



Features

- Recessed or surface mount applications
- Allows for side by side tape light installation for double the light output
- Made of lightweight high quality aluminum
- Frosted lens protects light source while evenly diffusing light
- Field cuttable extrusion and lenses
- Optional end caps available
- Compatible with all Trulux Tape Light
- Compatible all HD Snap Connectors

Available Lengths

39-3/8" (1 meter)

Available Finishes



Anodized Aluminum

Compatible Tape Light

- Trulux Single Color + HD Connectors
- Trulux Tunable CCT + HD Connectors
- Trulux RGB / RGBW / RGBTW + HD Connectors

TRULUX™ GTX Extrusion

The ultimate extrusion compatible with all Trulux tape light, the GTX is the perfect blend of utility and sleek design. Utilize the medium height profile to eliminate most dotting regardless of the light source while providing evenly diffused lighting. Need double the light output but limited on mounting space? No worries, as the GTX allows for side by side tape light installation for tape light widths 12mm or less (some soldering required).

Best suited applications:

Undercabinet, coves, architectural accent, task and ambient lighting

Ordering Information

PE-GTX-1M	1m GTX Aluminum Extrusion
PE-GTX-LENS-1M	1m Frosted Polycarbonate UV Lens
PE-GTX-END	GTX End Cap

