



Features

- Made of lightweight double anodized aluminum
- Frosted lens protects light source while evenly diffusing light
- Field cuttable extrusion and lens
- Aluminum provides excellent heat dissipation
- End caps provide a tailored look
- Mounting clips available for surface applications
- Compatible with most Trulux Tape Light

Available Lengths

- 39-3/8" (1 meter)
- 78-3/4" (2 meter)
- 118" (3 meter)

Available Finishes



Anodized Aluminum

Compatible Tape Light

- Trulux Single Color
- Trulux Tunable CCT (excludes Double Row)
- Trulux RGB

TRULUX™ Olin Extrusion

The Olin extrusion is sleek, slim and attractive. Use the UV lens and end caps to make a clean finished appearance. Standard surface E-CLIPs secure the extrusion to the surface for perpendicular light output; and the E-CLIP-45 allows angled placement (about 10° from perpendicular) for wall grazing effects, retail displays and task lighting.


Best suited applications:

Display cases, wall grazing, shelving, accent lighting

Ordering Information

PE-OLIN-1M	Olin Aluminum Extrusion (1 meter)
PE-OLIN-2M*	Olin Aluminum Extrusion (2 meter)
PE-OLIN-3M*	Olin Aluminum Extrusion (3 meter)
PE-UVLENS-1M	Frosted Polycarbonate UV Lens
PE-OLIN-FEED	Olin End Cap w/hole
PE-OLIN-END	Olin End Cap
E-CLIP	Surface Mount Clip

*Olin Extrusion (PE-OLIN-2M & PE-OLIN-3M) are available as special order only. Please allow up to 2 weeks for order processing.



Surface Mount Clip