



Features

- Custom built to specifications (allow 3-4 weeks lead time for special order)
- Transparent polycarbonate globes are shatterproof, weatherproof, and resistant to vibrations
- Rubber cable with injection molded nylon sockets supports spans up to 15 feet (use catenary cable for spans greater than 15 feet)
- cULus Listed
- Suitable for wet locations (IP68)

Available Globe Colors



Dimming Options

- Non-Dimmable

Listing / Ratings



Festoon Light String - 12V

Made to your specifications with watertight, shock resistant modules in 12V 3000K LED. When ordering, specify lead wire and tail wire lengths; globe color (Clear is standard); and socket type and spacing. For span distances greater than 15 feet, utilize catenary cable (sold separately). For horizontal mount to a wall or for vertical mount to shine upwards from a ledge, use LFS-CABLE-CLIP.

Technical Information

Series	LFS
Input Voltage	12V DC
CCT	3000K
CRI	74+
Wattage	Per Globe: 1W
Lumens	Up to 90Lm per ft
Max Run	300W
Cuttable	N/A
IP Rating	IP68
Dimmable	Not dimmable
Rating	cULus Listed for wet locations
Rated Life	80,000 hrs

Festoon Light String



FESTOON LIGHT STRING ORDERING INFORMATION

Special order - Please Allow Up To 2-4 Weeks Order Processing & Delivery*

ITEM NUMBER	CCT	LENGTH	LUMENS / FT	WATTAGE / GLOBE	IP RATING	CRI	CUTTING
LFS-12V-1-LED-WW	3000K	Custom	Up to 90Lm / ft	1W / globe	IP68	74+	N/A

When ordering Festoon Light String, be sure to specify socket spacing and total cable length (including lead and tail wire requirements). Designate the type of socket assembly to be factory-assembled on to stranded, tinned copper conductors in heavy-duty rubber cable. Festoon Light String is SPECIAL ORDER only; please allow 2-4 weeks for order processing. Request a sales quote online at <http://www.americanlighting.com/festoon-quote.html>.

FESTOON LIGHT STRING ACCESSORIES

ITEM NUMBER	DESCRIPTION
LFS-CABLE	12 gauge Festoon cable
LFS-BP	Mounting back-plate
LFS-CABLE-CLIP	Cable clips (qty 100)
LFS-GLOBE-CL	Clear Festoon Globe
LFS-GLOBE-BL	Blue Festoon Globe
LFS-GLOBE-PI	Pink Festoon Globe
LFS-GLOBE-PU	Purple Festoon Globe
LFS-GLOBE-RE	Red Festoon Globe
LFS-GLOBE-YE	Yellow Festoon Globe



LFS-CABLE



LFS-BP



LFS-CABLE-CLIP



LFS-GLOBE-CL
LFS-GLOBE-BL
LFS-GLOBE-PI
LFS-GLOBE-PU
LFS-GLOBE-RE
LFS-GLOBE-YE

Recommended Power Supplies



LED-DR 30 Driver
(30W capacity)

LED-DR30-12 (12V DC)



LED-DR 60 Driver
(60W capacity)

LED-DR60-12 (12V DC)



LED-DR 100 Driver
(100W capacity)

LED-DR100-12 (12V DC)



LED-DR 150 Driver
(150W capacity)

LED-DR150-12 (12V DC)