



## EPIQ 56 Downlight

### Features

- Excellent color rendering (90+ CRI)
- 2700K or 4000K color temperature
- Up to 1050 lumen output
- Consumes only 13.5 watts
- Use CLIQ trims for a squared finished
- Type IC and cETLus Listed for wet locations
- 35,000 hours rated life
- ENERGY STAR certified

### Available Finishes



White

### Listing / Ratings



### CLIQ 56 Trim



### Technical Information

Series	E56
Input Voltage	120V
CCT	2700K / 4000K
CRI	90+
Wattage	13.5W
Lumens	Up to 1050Lm
Beam Angle	84°
Dimmable	N/A
Mounting	Recessed mount (requires 5" & 6" housings)
Rating	cETLus Listed; Type IC; Suitable for wet locations
Rated Life	35,000 hrs

\*Minimum loads may apply

### Ordering Information

<b>E56-B27-WH</b>	5/6" White Baffle / 2700K / 1000Lm
<b>E56-B40-DB</b>	5/6" Dark Bronze Baffle / 4000K / 1050 Lumens
<b>Q56-B-WH</b>	5/6" Cliq Trim / White Baffle
<b>Q56-B-NK</b>	5/6" Cliq Trim / Nickel Baffle
<b>Q56-B-DB</b>	5/6" Cliq Trim / Dark Bronze Baffle
<b>Q56-WH</b>	5/6" Cliq Trim / White Smooth
<b>Q56-NK</b>	5/6" Cliq Trim / Nickel Smooth
<b>Q56-DB</b>	5/6" Cliq Trim / Dark Bronze Smooth
<b>E56-RING-DB</b>	5-6" Extender/Goof Ring
<b>E56-RING-WH</b>	5-6" Extender/Goof Ring

