



## Pro Dec G40 - E26

### Features

- SMD LED powered by on-board driver for 120V AC use in medium base (E26) sockets
- Nickel base resists corrosion
- Available in opaque lenses
- Dimmable with most CL or TRIAC dimmers\*
- IP65 rated for wet location use
- cULus Listed for indoor/outdoor use
- Sold in boxes of 25 and cases of 200

### Available Colors



2400K 2700K



Blue Green Red Yellow

### Dimming Options

- CL (10-100%\*)
- TRIAC (10-100%\*)

### Listing / Ratings



### Technical Information

|               |   |
|---------------|---|
| Series        | PG40/PG40F                                    |
| Base          | E26   |
| Input Voltage | 120V AC, 60Hz                                 |
| CCT           | 2400K/2700K/BL/GR/RE/YE                       |
| Wattage       | 1.2W  |
| Lumens        | Up to 48Lm (see individual product)           |
| IP Rating     | IP65  |
| Dimmable      | 10-100%*                                      |
| Rating        | cULus Listed; Suitable for indoor/outdoor use |
| Rated Life    | 25,000 hrs                                    |

\*Minimum loads will apply

Dimensions: 1-5/8" Dia. x 2-7/16" M.O.L.

### Ordering Information

|                     |  |
|---------------------|--|
| <b>PG40-E26-XWW</b> | Transparent / Deluxe Warm White (1900K) / 22Lm |
| <b>PG40-E26-UWW</b> | Transparent / Ultra Warm White (2400K) / 30Lm  |
| <b>PG40-E26-WW</b>  | Transparent / Warm White (2700K) / 36Lm        |
| <b>PG40-E26-WH</b>  | Transparent / Bright White (5500K) / 48Lm      |
| <b>PG40F-E26-BL</b> | Opaque Blue / E26 Base                         |
| <b>PG40F-E26-GR</b> | Opaque Green / E26 Base                        |
| <b>PG40F-E26-RE</b> | Opaque Red / E26 Base                          |
| <b>PG40F-E26-YE</b> | Opaque Yellow / E26 Base                       |