



## LED 3-Complete - 2400K/3000K/4000K

### Features

- 3-in-1 fixture design with selectable 2400K / 3000K / 4000K color temperatures
- High color rendering (up to 90+ CRI)
- Diffused lens eliminates dotting
- Up to 71 lumens per watt efficacy
- Linkable up to 150W
- Plug-in or direct wire capable
- Dimmable with most CL and ELV dimmers
- cETLus Listed for indoor dry locations
- 35,000 hours rated life
- ENERGY STAR certified

### Available Sizes

8" / 16" / 24" / 32"

### Available Finishes



White



Dark Bronze

### Dimming Options

- CL (5-100%)
- ELV (5-100%)

### Listing / Ratings



### Technical Information

Series	3LC
Input Voltage	120V AC, 60Hz
CCT	Selectable 2400K / 3000K / 4000K
CRI	80+ (2400K) / 90+ (3000K / 4000K)
Wattage	Up to 16.5W (see individual product)
Lumens	Up to 1100Lm (see individual product)
Beam Angle	120°
Max Run	150W
Dimmable	5-100%
Mounting	Surface mount
Rating	cETLus Listed (dry location)
Rated Life	35,000 hrs

### Ordering Information

<b>3LC-8-WH</b>	8" White / 6.4W / 420Lm
<b>3LC-8-DB</b>	8" Dark Bronze / 6.4W / 340Lm
<b>3LC-16-DB</b>	16" Dark Bronze / 12.8W / 690Lm
<b>3LC-24-DB</b>	24" Dark Bronze / 14W / 810Lm
<b>3LC-32-DB</b>	32" Dark Bronze / 16.5W / 910Lm

3LC fixtures include: (1) 3/8" cable connector / (1) End-to-end linking connector  
Captive mounting screws. LED Complete fixtures (ALC) are compatible with accessories from the LED Complete 2 (ALC2) and LED 3-Complete (3LC2).