172

DOWNLIGHTING



Features

- 3-in-1 5050 RGB LEDs every 0.33"
- 120° beam angle
- cETLus Listed⁺ for up to 65ft run lengths (can be field cut every 12" and maintain cETLus Listing)
- Suitable for indoor and outdoor use
- Sold as 65ft reels⁺
- Requires the use of Trulux Controller/Receiver Combo with Adaptive driver (when using included power connector kit; max run 50 feet or 24V DC Power Supply & RGB Controller Set (max run 65 feet)
- 30,000 hours rated life

Available Colors



Control Options

- 24V DC Power Supply & RGB Controller Set (max run 65 feet)
- Trulux DMX Controller/Receiver combo and Adaptive driver (max run 50 feet)

Listing / Ratings⁺



Polar 2 RGB Neon - 24V

Constructed with a durable PVC jacket and backing, the 24V DC Polar 2 RGB Neon is robust and reliable. Parallel wiring to each LED means if one LED goes out, the rest still get power. It is also highly energy efficient, using less than 3 watts per foot and possessing a 30,000 hour rated life. Choose from a variety of Trulux and other control options for preset color selection and dynamic effect lighting fades with speed control (50 foot max run) or 24V DC Power Supply & RGB Controller Set (65 foot max run).


Technical Information

| Series | RGB-NF | | | |
|---------------|---|--|--|--|
| Input Voltage | 24V DC | | | |
| ССТ | RGB | | | |
| Wattage | 2.7 watts per foot | | | |
| Max Run | 65 feet ⁺ | | | |
| Cuttable | Every 12" | | | |
| IP Rating | IP65** | | | |
| Dimmable | RGB / DMX Control* | | | |
| Rating | cETLus Listed ⁺ for indoor/outdoor use | | | |
| Rated Life | 30,000 hrs | | | |

*Requires the use of an RGB or DMX controller


**IP65 rated only when used with pre-attached molded power cord and end cap is properly sealed with dielectric grease, silicone and shrink tube

⁺ETL Listing for 24V Polar 2 RGB Neon is valid for lengths cut to 65 feet or less and only when factory installed (attached) power connection is used (American Lighting warrants up to 65 feet maximum run using 24V DC Power Supply & RGB Controller set; 50 feet max run with Trulux Controller/Receiver combo with Adaptive driver)



ARCHITECTURAL LIGHTING

POLAR 2 RGB NEON



Polar 2 RGB Neon 24V DC / 2.7W/ft

| POLAR 2 RGB ORDERING INFORMATION | | | | | | | |
|----------------------------------|-----|--------|-------------|--------------|-----------|-----|-------------|
| ITEM NUMBER | ССТ | LENGTH | LUMENS / FT | WATTAGE / FT | IP RATING | CRI | CUTTING |
| RGB-NF-24V-65 | RGB | 65 ft | N/A | 2.7W / ft | IP65 | N/A | 12" (305mm) |

Polar 2 RGB Reels Include: (1) 65ft reel / (1) Attached 5ft power connector kit (cETLus Listed) (4) Additional 5ft power connector kits (non-rated)

| POLAR 2 RGB ACCESSORIES | | | | |
|-------------------------|--|--|--|--|
| ITEM NUMBER | DESCRIPTION | | | |
| RGB-NF-CONKIT-NP | 24V power connector kit | | | |
| RGB-NF-JUMP.5 | 6" linking cables | | | |
| RGB-NF-JUMP3 | 3' linking cables | | | |
| RGB-NF-JUMP10 | 10' linking cables | | | |
| P2-NF-INVS | In-line splice | | | |
| P2-NF-CLIPS | Mounting clips (qty 10) | | | |
| RGB-NF-CHAN-3 | 3' Mounting channel | | | |
| DMX-3Z | 3 zone touch plate DMX wall controller | | | |
| REC-DMX-RJ45-5CH | Trulux DMX 5-channel receiver | | | |



RGB-NF-CONKIT-NP RGB-NF-JUMP3 RGB-NF-JUMP3 RGB-NF-JUMP10



RGB-NF-CHAN-3

DMX-3Z

REC-DMX-RJ45-5CH

P2-NF-INVS



P2-NF-CLIPS

Polar 2 RGB DMX Controller Set-up



RGB DMX Controller (3 Zone)

www.AmericanLighting.com

Adaptive Series Power Supply (30W / 60W / 96W / 192W / 288W)

2.2



+

Trulux DMX Receiver (Required) Polar 2 RGB

TRULUX LIGHTING SYSTEMS

TASK LIGHTING

DOWNLIGHTING