




Features

- Class 2, 12W 700mA constant current driver
- Compatible with ENCL-11 power supply enclosure
- Controls 1-3 LEDs in non-dimming applications
- Class II double insulation barrier for surge protection (no ground connection)
- Auto-reset protection for short circuit and over-voltage
- cURus Recognized (dry and damp locations)
- RoHs Compliant

Compatible Power Supply Enclosure (ENCL-11)



Listing / Ratings



700mA 12W Driver

The LED-DR12-700 features universal 94-264V AC power input with high reliability and Class 2 rating. This constant current driver powers 1-3 700mA LEDs in non-dimming applications. Its compact, sturdy design and fully isolated Class II design, allow it to cool by free air convection and operate at case temperatures from -22°F to 158°F in dry and damp locations.

Technical Information

Series	700mA
Max Load	12W
Minimum Load	3W
Input Voltage	100-240V AC, 50/60Hz
Output Current	700mA
Dimmable	N/A
Efficiency	82%
Input Wire	5" 18AWG
Output Wire	5" 18AWG
Operating Temp.	-22°F - 158°F (-30°C - 70°C)
Rating	cURus Recognized (dry and damp locations)
Dimensions	3-1/2"L x 1-5/8"W x 1-3/16"H

Ordering Information

LED-DR12-700	700mA - 12W Driver
---------------------	--------------------