



## Features

- Class 2, 25W 70mA constant current driver
- Controls 3-6 LEDs in non-dimming applications
- Class II double insulation barrier for surge protection (no ground connection)
- Auto-reset protection for short circuit and over-voltage
- cURus Recognized (dry and damp locations)
- RoHs Compliant

## 700mA 25W Driver

The LED-DR25-700 features universal 100-240V AC power input with high reliability and Class 2 rating. This constant current driver powers 3-6 700mA LEDs in non-dimming applications. Its compact, sturdy design and fully isolated Class II design, allow it to cool by free air convection and operate at case temperatures from -22°F to 158°F in dry and damp locations.

## Technical Information

Series	700mA
Max Load	25W
Minimum Load	8W
Input Voltage	100-240V AC, 50/60Hz
Output Current	700mA
Dimmable	N/A
Efficiency	83%
Input Wire	5" 18AWG
Output Wire	5" 18 AWG
Operating Temp.	-22°F - 158°F (-30°C - 70°C)
Rating	cURus Recognized (dry and damp locations)
Dimensions	3-3/8"L x 2-1/4"W x 1-1/8"H

## Listing / Ratings



## Ordering Information

<b>LED-DR25-700</b>	700mA - 25W driver
---------------------	--------------------