



Features

- 3000K color temperature with 90+ CRI
- 4" and 6" trim sizes with up to 1050 lumens
- Low profile design, as little as 1" high
- Quick and easy design for fast installs
- Polycarbonate lens for diffused soft light
- Dimmable with most ELV and TRIAC dimmers
- 35,000 hours rated life
- ENERGY STAR certified
- cETLus Listed for wet locations
- JA8 and Closet Rated (PIR only)

Available Finishes



White

Dimming Options

- TRIAC (10-100%)
 - CL (10-100%)
 - ELV (10-100%)
- (PIR is non-dimmable)

Listing / Ratings



(PIR) only

Quick Disc Series

The Quick Disc is a surface mount LED downlight for use with most standard junction boxes. Installation is fast and easy due to its unique screw-through mounting system that connects the downlight straight to the junction box. The Quick Disc is also available in a non-dimmable motion sensing version in both 4" and 6" sizes.

Technical Information

Series	QD
Input Voltage	120V AC, 60Hz
CCT	3000K / 4000K (QD6 only)
CRI	90+
Wattage	9W / 15W
Lumens	650Lm / 1050Lm
Beam Angle	120°
Dimmable	TRIAC / CL / ELV 10-100% / (PIR) non-dimmable
Mounting	Surface mount
Rating	cETLus Listed; Suitable for wet locations
Rated Life	35,000 hrs

Ordering Information

QD4-30-WH	Quick Disc 4" - White / 3000K / 650Lm / 9W / TRIAC
QD4PIR-30-WH	Quick Disc 4" - White / 3000K / 600Lm / 10W / 0-10V
QD6-30-WH	Quick Disc 6" - White / 3000K / 1050Lm / 15W / TRIAC
QD6-40-WH	Quick Disc 6" - White / 4000K / 1050Lm / 15W / TRIAC
QD6PIR-30-WH	Quick Disc 6" - White / 3000K / 950Lm / 15W / 0-10V

Quick Disc Series Downlights



QUICK DISC 4
QD4-30-WH
 120V AC / 3000K / 650Lm / 9W



QUICK DISC 6
QD6-30-WH
 120V AC / 3000K / 1050Lm / 15W
QD6-40-WH
 120V AC / 4000K / 1050Lm / 15W



QUICK DISC 4 PIR (Motion Sensor)
QD4PIR-30-WH
 120V AC / 3000K / 600Lm / 10W



QUICK DISC 6 PIR (Motion Sensor)
QD6PIR-30-WH
 120V AC / 3000K / 950Lm / 15W

TRULUX LIGHTING SYSTEMS

TASK LIGHTING

QUICK DISC
 DOWNLIGHTING

LINEAR LIGHTING

ARCHITECTURAL LIGHTING

POWER SUPPLIES