

TRULUX™ Single Color Controllers

1-100% full range dimming via dial or touch slide wall controls let you have full control over your Trulux system. Featuring ultra responsive touch controls and quality construction that will stand the test of time. No flickering, no signal wiring, and no input wiring; Simply mount to the wall and sync with Trulux receivers.



SRF-BATT

Trulux Push Dial Wall Control (Single Color / Single Zone)

- Push dial On/Off control dimmer
- Full range dimming (1-100%)
- Glass faceplate with satin nickel dial
- Wireless installation - No power wire
- Pair multiple receivers to a single control
- RF signal (up to 65 feet)
- Battery powered (CR2032)
- Requires Trulux receiver for install



RF

BATTERY

STATIC WHITE



SRF-4Z-3P

Trulux Touch Slide Wall Control (Single Color / 4 Zones / 3 Scenes)

- Touch On/Off control
- Touch slide control provides full range dimming (1-100%)
- Glass faceplate with back-lit buttons
- 3 programmable scenes
- 4 dedicated zone selection
- Pair multiple receivers to a single control
- RF signal (up to 65 feet)
- Requires 12V-24V DC input power wire and Trulux receiver for install



RF

STATIC WHITE

Trulux Controller Set-up



Push Dial Controller
(Single zone)

+



Adaptive LED Driver
(30W / 60W / 96W / 192W / 288W)

+



Trulux RF Receiver
(Required per zone)

+



Trulux Tape Light

TRULUX™ Single Color Accessories


Building a Trulux system is easy! Our Trulux controllers utilize wireless technology to make installation a breeze. All that's required is a 120V power source to a 12V/24V driver which is then fed to a Trulux receiver. Wire your tape to the receiver, sync the receiver to the controller, and you're all set.

TRULUX SINGLE ZONE



Single Zone Push Dial
Wireless RF Wall Controller
SRF-BATT

TRULUX 4 ZONE



4 Zone Touch Slide
RF Wall Controller
SRF-4Z-3P

PRIMARY SIDE DIMMING



CL / ELV / TRIAC
Standard Dimmer



Adaptive 24V Drivers
ADPT-DRJ-30-24 (30W)
ADPT-DRJ-60-24 (60W)
ADPT-DRJ-96-24 (96W)
ADPT-DRJ-192-24 (192W)
ADPT-DRJ-288-24 (288W)



Adaptive 24V Drivers
ADPT-DRJ-30-24 (30W)
ADPT-DRJ-60-24 (60W)
ADPT-DRJ-96-24 (96W)
ADPT-DRJ-192-24 (192W)
ADPT-DRJ-288-24 (288W)



Adaptive 24V Drivers
ADPT-DRJ-30-24 (30W)
ADPT-DRJ-60-24 (60W)
ADPT-DRJ-96-24 (96W)
ADPT-DRJ-192-24 (192W)
ADPT-DRJ-288-24 (288W)



Trulux RF Receiver
(Required per zone)
REC-5A-4Z



Trulux RF Receiver
(Required per zone)
REC-5A-4Z

Trulux Single Color Accessories



Trulink 4-in-1
Connector Kit
TL-CONKIT



Trulink 4-in-1
Connector Block
TL-BLKS (Qty 10)



HD Power Feed (IP54)
TL-2PWR-HD



HD Splice (IP54)
TL-2SPL-HD



HD Linking Cable (IP54)
TL-2JUMP6-HD (6")
TL-2JUMP24-HD (24")



Linking Cable (IP65)
TL-2JUMP65-.5 (6")
TL-2JUMP65-1 (12")
TL-2JUMP65-2 (24")