TRULUX LIGHTING SYSTEMS

TASK LIGHTING

DOWNLIGHTING

DECORATIVE LAMPS

LINEAR RGB
ARCHITECTURAL LIGHTING

POWER SUPPLIES

Features

- High impact dynamic linear RGB wall washer
- Durable aluminum alloy housing with enamel finish and tempered glass lens are fully sealed for use in wet locations (IP65)
- Built-in driver and five foot grounded power cord simplify installation
- Integrated mounting holes in base/leg brackets with adjustable tilt design for installation flexibility
- 60,000 hours rated life

NOTE: To use WW-L48-RGB with former RGB wall washers (LLW-RGB Series), item LW-WW-CONVERSION is needed for interconnection of signal cables (sold separately). Please contact American Lighting for more information

Available Finishes

Satin Aluminum

Listing / Ratings

RoHS COMPLIANT   WET LOCATION

Linear RGB Wall Washer

High power red, blue, and green LEDs combined with a durable aluminum housing rated for wet locations make this family of lighting tools perfect for high impact illumination, indoors or out. The Linear RGB fixtures must be powered directly with the attached five foot power cord, but allow data linking up to thirty fixtures.

Technical Information

Series	WW-L48-RGB
Input Voltage	120V AC, 60Hz
Wattage	45W
Linkable	Up to 30 fixtures
Beam Angle	25°
Dimmable	Requires DMX Controllers
Dimensions	47.25"W x 5"H x 2-3/16"D
Mounting	Surface mount
Rating	IP65 (wet location)
Rated Life	60,000 hrs

Ordering Information

WW-L48-RGB	48" Linear RGB Wall Washer
DMX-RGB-3	3-Channel DMX Controller
WW-EC15	15ft Signal Cable
WW-END	Signal Termination End Cap
WW-XLR3	3ft DMX Adapter cable
WW-XLR3-15	15ft DMX Adapter cable
CUSTOMCABLE	DMX Adapter or signal cable (special order)
WW-CON	DMX Controller for LED Wall Washers