

INSTALLATION INSTRUCTIONS

PATH-BLOOM



A WARNING

These products may represent a possible shock or fire hazard if improperly installed or attached in any way. Products should be installed in accordance with these instructions, current electrical codes, and/or the current National Electric Code (NEC).

MARNING

This product must be installed by a person familiar with the construction and operation of the product and the hazards involved and in accordance with current electrical codes and/or the current National Electric Code (NEC). Consult a local licensed electrician if you are unsure of or have questions about installation.

SAFETY INFORMATION

- Read all instructions before beginning. Save these instructions for future use.
- To reduce the risk of fire, electric shock, or injury to persons, pay close attention to this manual and stay within its guidelines when using this product.
- To reduce the risk of fire, electric shock, or injury to persons, this fixture must be properly grounded.
- This product requires a 12V AC or 12V DC power input. Confirm source voltage prior to installation and use appropriate 12V AC transformer or 12V DC driver.
- Disconnect supply power at the source prior to installation.
- Do not remove any parts from this fixture. This fixture has no serviceable parts.
- As needed, clean lens with non-abrasive cleaning solution and soft cloth.
- · LEDs are bright. Do not look directly into fixtures.
- This product is suitable for use in wet locations and marine environments. It is designed for outdoor use only.
- · Do not use this fixture in dimming circuits.
- The path light should be mounted to a level concrete surface.
- Anchor bolts included are for concrete installation. For all other applications, use anchors suitable for the mounting surface.

INSTALLATION (SEE FIGURE 1):

Disconnect supply power from source prior to installation.

- Using the fixture base as a template, mark the locations of the four expansion anchor bolts onto the level concrete surface.
- 2. Install expansion anchors in marked locations.
- 3. Connect the fixture's lead wires to the supply wires, matching polarity: Black to Black/Hot, White to White/Neutral and Green to Bare/Ground using included wire nuts.
- 4. Line up path light base's mounting holes with expansion anchors.
- 5. Tighten the anchor screws with flat washers and lock washers in place, making sure wires are not pinched in any way.

If installing into soil, use PATH-SMS (sold separately) and follow those instructions.

