

## INSTALLATION INSTRUCTIONS

### PATH-BURG



#### ⚠ WARNING

These products may represent a possible shock or fire hazard if improperly installed or attached in any way. Products should be installed in accordance with these instructions, current electrical codes, and/or the current National Electric Code (NEC).

#### ⚠ WARNING

This product must be installed by a person familiar with the construction and operation of the product and the hazards involved and in accordance with current electrical codes and/or the current National Electric Code (NEC). Consult a local licensed electrician if you are unsure of or have questions about installation.

#### SAFETY INFORMATION

- Read all instructions before beginning. Save these instructions for future use.
- To reduce the risk of fire, electric shock, or injury to persons, pay close attention to this manual and stay within its guidelines when using this product.
- To reduce the risk of fire, electric shock, or injury to persons, this fixture must be properly grounded.
- This product requires a 12V AC or 12V DC power input. Confirm source voltage prior to installation and use appropriate 12V AC transformer or 12V DC driver.
- Disconnect supply power at the source prior to installation.
- Do not remove any parts from this fixture. This fixture has no serviceable parts.
- As needed, clean lens with non-abrasive cleaning solution and soft cloth.
- LEDs are bright. Do not look directly into fixtures.
- This product is suitable for use in wet locations and marine environments. It is designed for outdoor use only.
- Do not use this fixture in dimming circuits.
- The path light should be mounted to a level concrete surface.
- Anchor bolts included are for concrete installation. For all other applications, use anchors suitable for the mounting surface.

#### INSTALLATION (SEE FIGURE 1):

Disconnect supply power from source prior to installation.

1. Remove the four retaining screws near the base of the path light and take off the mounting bracket.
2. Using the mounting bracket as a template, mark the locations of the four expansion anchor bolts onto the level concrete surface. Remember to orient the bracket in the orientation desired for the path light fixture once installed.
3. Install expansion anchors in marked locations.
4. Connect the fixture's lead wires to the supply wires, matching polarity: Black to Black/Positive (+) and White to White/Negative (-) using included wire nuts.
5. Line up path light base with the mounting bracket, making sure wires are not pinched in any way.
6. Replace the retaining screws.

If installing into soil, use PATH-SMS (sold separately) and follow those instructions.

